

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 November 2003 (20.11.2003)


PCT

(10) International Publication Number
WO 03/095916 A1

- (51) International Patent Classification⁷: **F26B 5/12, 5/14**
- (21) International Application Number: **PCT/GB03/01743**
- (22) International Filing Date: **24 April 2003 (24.04.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0210523.7 **8 May 2002 (08.05.2002) GB**
- (71) Applicant (for all designated States except US): **O. N. BECK & CO. LTD.** [GB/GB]; 104, Fox Lane, London N13 4AX (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BECK, Clifford, Howard, Berthold** [GB/GB]; 104 Fox Lane, London N13 4AX (GB).
- (74) Agent: **FORRESTER KETLEY & CO**; Forrester House, 52 Bounds Green Road, London N11 2EY (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DE-WATERING ARTICLES



(57) Abstract: A method of de-watering an article (3) subjected to processing, such as pasteurising, in which water collects in a depression in a surface (2) of the article, comprises passing the article beneath a suction device (4) so that the said surface of the article passes underneath the suction device in proximity to an inlet (6) of the suction device, directing at last one jet of compressed air through a nozzle (10) at the depressed surface of the article as the said surface passes by the inlet of the suction device to displace the water from the said surface of the article into the air adjacent to the inlet of the suction device, and operating the suction device to draw the water-containing air into the inlet of the suction device. An apparatus for carrying out the de-watering method employs a Coanda effect air moving device as the suction device (4) and one or more air jet nozzles located at the inlet opening of the air moving device.

WO 03/095916 A1